

HIGH VISIBILITY GRILL

Lets you see what you're doing regardless of the trencher's angle.

NEW DANGER BAR

25% Bigger for increased durability. Reduces crumpler flexing producing a better finish.

RAISED MOTOR

The motor is housed above the spoil to ensure maximum protection from rocks and debris.



DURABLE SCRAPER SHOE

The scraper shoe is now made from steel for increased durability.

HEAD START CRUMBER

Start trenching with the crumber in the ground eliminating the need to step out of the machine once the trench is started, saving you time & money.

TWIN SPOIL AUGERS

Ensures efficient spoil removal on both sides of the trench. Can be detached for trenching close to walls or fences.

WHY A TRENCHER OVER A BUCKET?



EFFICIENT

NARROWER TRENCHES TO GREATER DEPTHS CAN BE ACHIEVED



FASTER

A TRENCHER WILL CUT GROUND FASTER THAN AN EXCAVATOR BUCKET AS IT CUTS IN A CONTINUOUS MOVEMENT



EASIER

THE SPOIL IS EXCAVATED MORE FINELY WITH A TRENCHER SO THE TRENCH CAN BE EASILY BACKFILLED WITH BETTER COMPACTION. AS THE SPOIL IS MUCH FINER IT IS SUITABLE FOR THE BEDDING OF PIPES AND CABLES ETC



ACCURATE

VARIOUS SIZE TRENCH WIDTHS MEANS YOU DON'T HAVE TO EXCAVATE ANY MORE THAN IS REQUIRED. LEAVES THE BOTTOM OF THE TRENCH FLAT AND CLEAN



COST EFFECTIVE

DIGS 3 TO 4 TIMES FASTER THAN AN EXCAVATOR/BACKHOE WITH LESS MESS. SPOIL IS EASIER TO BACKFILL WITH BETTER COMPACTION

HYDRIVE TRENCHER

Digga Hydrive Trenchers, compact and powerful fitted with a quality Digga Planetary Drive & Eaton Hydraulic Motor. Unique drive system positioning allows for more usable horse power providing greater efficiency.

Features:

- Head Start crumber system (patent pending) - start trenches with the crumber bar in the down position. Save time by not having to get off the machine
- Hydrive: Up to 1200mm digging depth and 300mm digging width with a 42mm chain
- Hydrive XD: Extra Heavy Duty Trencher for up to 1200mm digging depth and 350mm trenching width with a 50.8mm chain
- Twin spoil augers for efficient spoil removal on both sides of the trench, creating finely crumbed spoil for effective re-compaction and minimal ground disturbance
- Frame can be side-shifted for digging close to permanent structures
- Augers can be removed for close-up trenching to walls or fences
- 3 different chain options, Earth, Combo and Diggatac

Machine suitability:

Hydrive - Excavators up to 4.5tonne, Skid Steer Loaders, Mini Machines

Hydrive XD - Excavators 4.5 - 8 tonne, Large Skid Steer Loaders
Tele-handlers, Back Hoes



	900	1200	XD 1200
Cutting Depth	Up to 900mm	Up to 1200mm	Up to 1200mm
Cutting Width (mm)	100 / 150 / 200 / 250 / 300	100 / 150 / 200 / 250 / 300	150 / 200 / 250 / 300 / 350
Recommended Flow (lpm)	50-80	50-80	60-115
Motor Type	2K Bell EATON	2K Bell EATON	2K Bell EATON
Max Pressure - Do not exceed	240 Bar @ 60 lpm	240 Bar @ 60 lpm	240 Bar @ 60 lpm
Max Flow - Do not exceed	75 lpm @ 200 bar	75 lpm @ 200 bar	115 lpm @ 130 bar
Max Continuous Power	25 Kw (34 hp)	25 Kw (34 hp)	25 Kw (34 hp)
Length (mm)	1,888	2,160	2,478
Horizontal Height (mm)	802	802	957
Width (mm)	1,212	1,212	1,212
Skid Steer Loader: Std Flow	✓	✓	-
Skid Steer Loader: High Flow	✓	✓	✓
Backhoe	-	-	-
Excavator: 3.5-8t	-	-	-

